## NAUTILUS

**Naval** Inertial Navigation Family





## The NAUTILUS FAMILY

The **NAUTILUS** family of strapdown Fiber Optic Gyro (FOG) Naval Inertial Navigation Systems (INS) is designed for performance scalability up to high-grade position accuracy and long endurance missions.

The proprietary ITAR-free FOG-based sensor technology coupled with advanced state estimation techniques based on Kalman Filter algorithm, provides the best-value solution for Gyrocompass, AHRS (Attitude Heading Reference Systems) and Positioning in an all-in-one maintenance-free product, compact, light and reliable.

Specifically aimed at maritime navigation, **NAUTILUS** family is engineered to guarantee performance in severe environments, both with or without GNSS and Speed Log aiding, and to allow flexible and easy integration in retrofit programs and in new vessels' installations.



CHARACTERISTICS	NAUTILUS 4000	NAUTILUS 3000	NAUTILUS 2000	NAUTILUS 1000
Heading (RMS)	< 0.025° sec LAT	< 0.05 sec LAT	< 0.1 sec LAT	< 0.5 sec LAT
Roll / Pitch (RMS)	< 0.01°	< 0.01°	< 0.01°	< 0.1°
Heave (RMS)	< 2.5 cm or 2.5%	< 5 cm or 5%	< 5 cm or 5%	N.A.
Position (CEP50)	< 1nm/8hr	< 1nm/2hr	< 4 nm/hr	N.A.
Alignment time (data availability)	10 minutes	10 minutes	10 minutes	10 minutes
Alignment time (full accuracy)	30 minutes	30 minutes	30 minutes	30 minutes
IMO (MED/96/98/EC)	compliant	compliant	WheelMark	compliant

## **SYSTEM CHARACTERISTICS**

Interfaces

RS422/RS232 Ethernet PPS

Data Output Rate: *up to 100 Hz* Input/Output Standards: *Binary, NMEA0183* 

**Environmental and Reliability** 

Operating Temperature: -20°C to +55°C Storage Temperature: -40°C to +80°C EMC/EMI: MIL-STD-461F or IEC 60945 Vibration: MIL-STD-167-1A or IEC 60945

MTBF: > 45000 hours Waterproofness: IP66 **Dimensions** 

WxHxD: 151x161x286

Weight

8.5 Kg

Power requirements 28VDC (18-36VDC): <15 W

