## PETRA

## **Land Inertial Navigation Family**





## The PETRA FAMILY

The **PETRA** family of Land Inertial Navigation Systems (INS) best exploits the strapdown Fiber Optic Gyro (FOG) technology for high-precision pointing, localization and navigation achieving optimal performance.

Thanks to innovative integration of ITAR-free inertial sensors, designed and manufactured in Italy, with advanced state estimation techniques based on Kalman Filter algorithm, completely developed and tuned in-house, the **PETRA** family provides the end user with superior pointing accuracy in GNSS denied environment.

Aimed to withstand harsh operational conditions, **PETRA** is ideally suited for new and retrofit land vehicles programmes.

The **PETRA** products family provides maintenance-free, robust, low weight, compact volume land inertial navigation and pointing solutions without compromising performance in all operational environments.



| CHARACTERISTICS                    | PETRA 2000               | PETRA 1000               |
|------------------------------------|--------------------------|--------------------------|
| Heading (RMS)                      | < 1 mils secant latitude | < 5 mils secant latitude |
| Roll / Pitch (RMS)                 | < 0.3 mils               | < 1 mils                 |
| Horizontal Position with VMS       | 0.25 % DT                | 0.6% DT                  |
| Vertical Position with VMS         | 0.1% DT                  | 0.6% DT                  |
| Horizontal Position with GPS (RMS) | <10 m                    | < 10m                    |
| Vertical Position with GPS (RMS)   | <10 m                    | < 10m                    |
| Alignment time (Static)            | 2 minutes                | 2 minutes                |
| Alignment time (full accuracy)     | 15 minutes               | 15 minutes               |

## SYSTEM CHARACTERISTICS

**Interfaces** 

RS422/RS232 Ethernet CAN Bus MIL-PRF-71196

Data Output Rate: up to 500 Hz

**Environmental and Reliability** 

Operating Temperature: -32°C to +65°C Storage Temperature: -40°C to +71°C EMC/EMI: MIL-STD-461F Vibration: MIL-STD-810F Method 514.5, cat. 20

MTBF: > 40000 hours

Dimensions

WxHxD: 151x161x286

Weight

8.5 Kg

**Power requirements** 28VDC (18-36VDC): <15 W



CONTACT US: